Page 1 of 4 Thursday, March 20, 2003

MSDS - Material Safety Data Sheet Product Name: LIQUID WRENCH SUPER LUBRICANT (POUR)

MSDS No.: L204

L Basic Information:						
Manufacturer: RADIATOR SPECIALTY COMPANY			NFPA (
Address: P.O. BOX 159, 600 RADIATOR ROAD			Health Reactivity			
City, ST Zip: INDIAN TRAIL, NC 28079			Health Reastivity 2 0			
Emergency Contact: Rocky Mountain Poision	Control Center					
Emergency Telephone Number: 303-623-5716			Special			
Contact: Robert Geer				\sim		
Information Telephone Number: 704-688-3430			2 Health			
Last Update: 03/20/2003			2	Flammability		
Chemical State: X Liquid Gas Solid			0 Reactivity			
Chemical Type: Pure X M	ixture		c	Pers. Protection		
II. Ingredients:						
Trade Secret						
	E	HS IARO		SHA ACGIH	Other	
CAS No. Chemical Name	% Range	NŢP	SUB Z PE		Limits	
111-76-2 2-Butoxy-1-Ethanol	1-5		X 50) ppm 25 ppm		
64742525 Naphthenic Petroleum Disti	llate 70-100	70-100		5 mg/m3 (m 5 mg/m3 (m		
III. Hazardous Identification:						
Hazard Category:						
X Acute Chronic	X Fire	X Fire		re [Reactive	
Hazardous Identification Information: Danger: Harmful or fatal if swallowed. C	Combustible. Eye and sk	kin irritant.				
IV. First Aid Measures:						
Route(s) of Entry:						
Absorption, Inhalation, and Ingestion.						
Health Hazards (Acute and Chronic):						
Signs and Symptoms:						

Eye Contact: Irritant. Prolonged contact may cause conjunctivitis. Skin Contact: Irritant. Defatting of tissue, dermatitis may occur.

Inhalation: Irritant to mucous membranes. Repeated exposure may cause narcosis, dizziness, respiratory or lung irritation.

Ingestion: HARMFUL OR FATAL IF SWALLOWED. May cause burns to mouth, throat & stomach.

Medical Conditions Generally Aggravated by Exposure:

Page 2 of 4 Thursday, March 20, 2003

MSDS - Material Safety Data Sheet Product Name: LIQUID WRENCH SUPER LUBRICANT (POUR)

MSDS No.: L204

Emergency and First Aid Procedures:

Eye Contact: Flush eyes with clean water for 15 minutes while lifting eyelids. Get prompt medical attention.

Skin Contact: Wash with soap and water thoroughly. If adverse effects persist, get prompt medical attention. Launder contaminated clothing before reuse.

Inhalation: Remove to fresh air. If breathing becomes difficult give oxygen and get prompt medical attention. If breathing stops, give artificial respiration and get prompt medical attention.

Ingestion: DO NOT INDUCE VOMITING! Call Poison Control Center, physician, or hospital emergency room immediately. Aspiration of vomitus into the lungs can cause pneumonitis, which can be fatal.

Other Health Warnings:

Vomiting and subsequent aspiration into the lungs may lead to chemical pneumonia and pulmonary edema which is a potentially fatal condition.

V. Fire Fighting Measures:

Flash Point: 140F Lower Explosive Limit: N/E Upper Explosive Limit: N/E

F.P. Method: TCC

Fire Extinguishing Media: Water Fog, Foam, Carbon Dioxide, Dry Chemical

Special Fire Fighting Procedures:

Wear self-contained positive pressure breathing apparatus and protective clothes. Cool containers with a water fog. Do not use forced water stream as this could cause the fire to spread. Use equipment or shielding to protect personnel against venting, rupturing, or bursting containers.

Unusual Fire and Explosion:

None known

VI. Accidental Release Measures:

Steps to be Taken in Case Material is Released or Spilled:

Eliminate all ignition sources. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Dike or contain spill and absorb with inert materials (sand, sawdust, absorbent sweeping compounds, rags, etc). Place contaminated material into an approved chemical waste container. Where possible, vacuum spilled liquid using an explosion proof vacuum to recover material. Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occured.

VII. Handling and Storage:

Precautions to be Taken:

Handling: Use with adequate ventilation and proper protective equipment.

Store in a cool, dry area, away from oxidizers. Keep away from open flames, sparks, or other iginition sources.

Other Precautions:

Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye. KEEP AWAY FROM CHILDREN AND ANIMALS! Danger: Flammable.

Page 3 of 4 Thursday, March 20, 2003

MSDS - Material Safety Data Sheet Product Name: LIQUID WRENCH SUPER LUBRICANT (POUR)

MSDS No.: L204

VIII. Exposure Controls/Personal Protection:

Ventilation Requirements:

Use with adequate ventilation. If TLV is exceeded, wear NIOSH approved respirator.

Personal Protective Equipment:

See Section 2 for applicable exposure limits. For prolonged exposure wear protective safety glasses, gloves, and apron.

IX. Physical and Chemical Properties:

Boiling Point: 320 F Melting Point: N/A

Evaporation Rate (Butyl Acetate = 1): N/A

Specific Gravity (H20 = 1): 0.90400

Vapor Pressure (mm Hg.): N/A

Vapor Density (AIR = 1): N/A

Solubility In Water: Insoluble Appearance and Odor: Clear light yellow with sweet vanilla odor

Other Information:

X. Stability and Reactivity:

Stability:

Product is stable

Incompatibility (Materials to Avoid):

Avoid contact with strong oxidizers

Decomposition/By Products:

Normal products of combustion, smoke, carbon dioxide, carbon monoxide, and sulfur trioxides.

Hazardous Polymerization:

Will not occur

XI. Toxicological Information:

Not Established

XII. Ecological Information:

Not Established

XIII. Disposal Considerations:

DISPOSAL: This container may be recycled when empty. Before offering for recycling, empty the can by using the product according to the label. If recycling is not available, wrap the container and discard in the trash. Dispose of unused product in accordance with all local, state government and federal laws and regulations.

XIV. Transport Information:

DOT Shipping Name: Not DOT regulated.

DOT Hazard Class: None

Page 4 of 4 Thursday, March 20, 2003

MSDS - Material Safety Data Sheet Product Name: LIQUID WRENCH SUPER LUBRICANT (POUR)

MSDS No.: L204

XV. Regulatory Information:

See Section 2 for SARA Reportable Chemicals.

USA TSCA: All components of this material are listed on the US TSCA Inventory.

Warning: This product contains a chemical(s) known to the State of California to cause cancer or birth defects or other reproductive harm.

XVI. Other Information:

Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye. KEEP AWAY FROM CHILDREN AND ANIMALS!

N/E: Not Established N/D: Not Determined N/A: Not Applicable N/AV: Not Available

While Radiator Specialty Company believes this data is accurate as of the revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered soley for information, investigation, and verification. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is repsonsible for full compliance.